EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 16516:2017+A1

July 2020

ICS 13.040.20; 91.100.01

Supersedes EN 16516:2017

English Version

Construction products: Assessment of release of dangerous substances - Determination of emissions into indoor air

Produits de construction : Évaluation de l'émission de substances dangereuses - Détermination des émissions dans l'air intérieur Bauprodukte: Bewertung der Freisetzung von gefährlichen Stoffen - Bestimmung von Emissionen in die Innenraumluft

This European Standard was approved by CEN on 9 July 2017 and includes Amendment 1 approved by CEN on 24 May 2020.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents

Page

European forewordIntroduction		4
		5
1	Scope	7
2	Normative references	7
3 3.1 3.2	Terms, definitions and abbreviations Terms and definitions Abbreviations	8
4 4.1 4.2 4.3	Intended conditions of use, emission scenarios and European reference room Intended conditions of use and emission scenario Reference room and emission scenario Time schedule of emission(s) determination	14 15
5 5.1 5.2 5.3 5.4	Product sampling and transport to the laboratory General Objective of sampling Preparation of a sampling plan and sampling strategy Information from the testing laboratory needed to complement the product	16 16 16
5.5 5.6 5.7 5.8	sampling plan Packaging and transport of laboratory sample Sample description, marking of laboratory samples and the sampling report Chain of custody report Dispatch of product samples, time schedule	18 19 19
6 6.1 6.2	Handling of product samples in the laboratory Storage of sample in the testing laboratory Preparation of the test specimen	20
7 7.1 7.2 7.3	Test chamber conditions Principles Dimensions of test specimen Loading factor	21 21
7.4 7.5 7.6 7.7	Ventilation Air velocity Cleanliness of test chamber Testing climate (temperature, relative humidity of supply air)	22 22 22
7.8 7.9 7.10 7.11	Storage of test specimen Large products or inhomogeneous products Volume of test chamber Placement of test specimen in test chamber	22 23 23
8 8.1 8.2 8.3	Determination of vapour-phase A deleted text (A compounds in test chamber air Common requirements Determination of VOCs and SVOCs in test chamber air Determination of formaldehyde and some other volatile and very volatile carbonyl	23 23
8.4 8.5	compounds in test chamber air A) Determination of ammonia in test chamber air Other general aspects of quality control	33

9	Calculation of specific emission rates and expression of results at the reference room	35
10	Reporting for the horizontal reference method	
10.1	General	
10.2	Sampling	
10.3 10.4	Handling of samples in the laboratory, preparation of test specimen Test chamber conditions	
10.4 10.5	Determination of vapour-phase organic compounds A and ammonia A in test	
10.6	chamber air Calculation and reporting of test results	
11	Indirect methods	40
Annex A (informative) Repeatability and reproducibility		41
A.1	Repeatability	41
A.2	Reproducibility	41
Annex	B (informative) Examples of indirect methods (also called simplified, screening, secondary, derived or alternative methods)	43
B.1	General	43
B.2	Indirect methods-emissions testing	43
B.3	Indirect methods specifying alternative procedures	44
B.4	Other secondary methods — Prediction of results at specified time	44
Annex	C (informative) Information on very volatile organic compound (VVOC) testing	45
Annex	D (informative) Example of a form for the sampling report	46
Annex	E (informative) Example form for a chain of custody report	47
Annex	F (informative) Benzene artefact generation on Tenax	48
Annex	G (normative) List of non-carcinogenic VOCs	49
Annex	H (informative) List of carcinogenic VOCs	57

European foreword

This document (EN 16516:2017+A1:2020) has been prepared by Technical Committee CEN/TC 351 "Construction Products: Assessment of release of dangerous substances", the secretariat of which is held by NEN.

Amendment 1 is a complement to EN 16516:2017. It concerns the measurement of ammonia emissions from construction products.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2021, and conflicting national standards shall be withdrawn at the latest by January 2021.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document includes Amendment 1 approved by CEN on 24 May 2020.

This document supersedes ♠ EN 16516:2017 ♠.

The start and finish of text introduced or altered by amendment is indicated in the text by tags A_1 .

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

This European Standard was developed under the remit of Mandate M/366 'Development of horizontal standardized assessment methods for harmonised approaches relating to dangerous substances under the Construction Products Directive (CPD)', addressing the preparation of horizontal measurement/test methods for the determination of emission of regulated dangerous substances from construction products into indoor air, soil, surface water and ground water. This mandate is a complement to the product mandates granted by the European Commission to CEN under European law for construction products. The harmonized products standards (hEN) developed in CEN under mandates from the European Commission specify construction product(s) as put on the market and address their intended conditions of use. The text of Mandate M/366 is available at www.centc351.org.

Details of relevant European or national regulations are available in the "TRIS database" [1].

This European Standard has gone through a robustness validation for identifying how small changes in specific testing parameters can influence the test result. This study also delivered data on repeatability within one testing laboratory (see Annex A) and has since been expanded to include reproducibility data from further round robin tests between different laboratories (see Annex A).

The responsibility for product specification lies with the product TCs, as described in CEN/TR 16496. This determination of emission into indoor air is carried out on products under their intended conditions of use. The intended use of a construction product is generally specified in the corresponding harmonized product standard. The specific emission rates determined using this European Standard are associated with application of the product in a defined European Reference Room under specified climate (temperature and humidity) and ventilation conditions. Converting the test results into a concentration in the air of the reference room is essential because it is not possible to evaluate emissions in all possible use scenarios.

The reference room dimensions, associated product loading factors, as well as climate and ventilation conditions are selected to represent the general indoor environment (see Clause 4). Based on the huge amount of available European experience, it was possible to identify one emission scenario and one reference room and associated set of product loading factors to be used.

This European Standard specifies the horizontal reference method for testing the emission (release) of dangerous substances from construction products into indoor air. This method uses a test chamber in which emissions are generated under conditions which are kept constant during the test. These conditions are selected so that the test results can be expressed in terms of concentrations of dangerous substances in the air of the reference room (see Clause 7 and Clause 9). It should be noted that the test chamber is defined in terms of performance requirements. This responds to the requirement of Mandate M/366 for a horizontal approach while maintaining sufficient flexibility on chamber dimensions to ensure representative samples of different materials can be accommodated (see Clause 5). Clause 8 of this European Standard specifies how emitted regulated dangerous substances should be analysed.

This European Standard also addresses separately (see Clause 11 and Annex B) indirect methods that provide a result that is comparable or that correlates with the result of the reference method within their specified field of application. Such methods may be easier and/or cheaper to apply. They are in accordance with Mandate M/366 provided that their comparability or correlation to the reference test method has been demonstrated in their specific field of application.

The selection of one emission scenario and one reference room for evaluating emissions to indoor air is in general accordance with the approach taken in existing European national regulations and voluntary schemes relating to emissions from construction products into indoor air. It also accords with the horizontal requirements of Mandate M/366. The aim of this European Standard is not to develop a new testing method but to combine by normative references the use of existing standards. This approach is complemented, when necessary, with additional and/or modified requirements to ensure all

construction products are evaluated under comparable conditions as required by the horizontal concept specified in Mandate M/366.

In summary, the horizontal test method specified in this European Standard determines the specific emission rate of vapour phase organic compounds from a construction product into indoor air. This can be converted into a concentration in the air of the reference room by calculation.

This European Standard has not been evaluated for the determination of 'steady-state' concentration of formaldehyde.

NOTE A European Standard (EN 717–1) exists for the determination of formaldehyde emissions from woodbased panels, in terms of 'steady-state' concentrations.

1 Scope

(A) This document specifies a horizontal reference method for the determination of emissions of regulated dangerous substances from construction products into indoor air. This method is applicable to volatile organic compounds, semi-volatile organic compounds, very volatile aldehydes and ammonia. It is based on the use of a test chamber and subsequent analysis of the organic compounds by GC-MS, HPLC, and for ammonia, subsequent analysis by spectrophotometric methods or any equivalent analytical methods (such as ion chromatography and ammonium specific electrode). (A)

NOTE 1 Supplemental information is given on indirect test methods (see Annex B) and on measuring very volatile organic compounds (see Annex C).

NOTE 2 This European Standard describes the overall procedure and makes use of existing standards mainly by normative reference, complemented when necessary with additional or modified normative requirements.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CEN/TR 16220:2011, Construction products - Assessment of release of dangerous substances - Complement to sampling

EN 16687, Construction products - Assessment of release of dangerous substances - Terminology

EN ISO 13137, Workplace atmospheres - Pumps for personal sampling of chemical and biological agents - Requirements and test methods (ISO 13137)

EN ISO 16000-9:2006, Indoor air - Part 9: Determination of the emission of volatile organic compounds from building products and furnishing - Emission test chamber method (ISO 16000-9:2006)

EN ISO 16000-11, Indoor air - Part 11: Determination of the emission of volatile organic compounds from building products and furnishing - Sampling, storage of samples and preparation of test specimens (ISO 16000-11)

EN ISO 16017-1, Indoor, ambient and workplace air - Sampling and analysis of volatile organic compounds by sorbent tube/thermal desorption/capillary gas chromatography - Part 1: Pumped sampling (ISO 16017-1)

ISO 554, Standard atmospheres for conditioning and/or testing — Specifications

A) ISO 7150-1, Water quality — Determination of ammonium — Part 1: Manual spectrometric method (A_1)

ISO 16000-3, Indoor air — Part 3: Determination of formaldehyde and other carbonyl compounds in indoor air and test chamber air — Active sampling method

ISO 16000-6, Indoor air — Part 6: Determination of volatile organic compounds in indoor and test chamber air by active sampling on Tenax TA sorbent, thermal desorption and gas chromatography using MS or MS-FID